

Weatherproof Box Two Gang

Standard: UL514A and CSA C22.2 No.18.1-13
Material: Aluminum
Application: For use in branch circuit wiring in wet, damp or dry locations



3 HOLES



4 HOLES



5 HOLES



5X HOLES



7 HOLES



7X HOLES



9 HOLES

Topele	Trade Size	Shelf QTY	Master QTY	Widh(inch)	Length(inch)	Depth(inch)	Max. Capacity
TGB50-3	1/2"X3	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB75-3	3/4"X3	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB50-4	1/2"X4	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB75-4	3/4"X4	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB50-5	1/2"X5	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB75-5	3/4"X5	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB100-5	1"X5	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB50-5X	1/2"X5	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB75-5X	3/4"X5	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB100-5X	1"X5	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB50-7	1/2"X7	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB75-7	3/4"X7	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB50-7X	1/2"X7	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB75-7X	3/4"X7	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB50-9	1/2"X9	1	40	4.530	4.530	2.160	30.5cu in / 500ml
TGB75-9	3/4"X9	1	40	4.530	4.530	2.160	30.5cu in / 500ml
DTB50-5	1/2"X5	1	40	4.530	4.530	2.625	37.3cu in / 611ml
DTB75-5	3/4"X5	1	40	4.530	4.530	2.625	37.3cu in / 611ml
DTB100-5	1"X5	1	40	4.530	4.530	2.625	37.3cu in / 611ml
DTB50-5X	1/2"X5	1	40	4.530	4.530	2.625	37.3cu in / 611ml
DTB75-5X	3/4"X5	1	40	4.530	4.530	2.625	37.3cu in / 611ml
DTB100-5X	1"X5	1	40	4.530	4.530	2.625	37.3cu in / 611ml
DTB50-7X	1/2"X7	1	40	4.530	4.530	2.625	37.3cu in / 611ml
DTB75-7X	3/4"X7	1	40	4.530	4.530	2.625	37.3cu in / 611ml
DTB100-7X	1"X7	1	40	4.530	4.530	2.625	37.3cu in / 611ml

Nota: Boxes supplied with 2 closure plugs, 1 green grounding screw and 2 mounting lugs with self-tapping screws. The color of boxes will be in grey, unless any other color is specified.

Aluminum Stamped Cover with Gasket & Screws



CAT# SBC-2



CAT# DBC-4



CAT# RBC-2